

作成承認印	配布許可印
	

Nikon F100

FAA35051

REPAIR MANUAL

Nikon | NIKON CORPORATION
Tokyo, Japan

Copyright © 1998 by Nikon Corporation.
All Rights Reserved.
無断転載を禁ず !!

Specifications

1.	Photometry	M 1
2.	TTL auto-flash control	M 1
3.	A F	M 1
4.	Finder	M 1
5.	In-finder LCD back light	M 2
6.	Superimpose display	M 2
7.	The switches for mechanism	M 2
8.	Preview function	M 2
	The figure of preview sequence	M 3
9.	The contacts for power pack	M 4
10.	The contacts on the rear cover for connection with the camera	M 4
11.	Shutter	M 4
12.	Program diagram	M 5
13.	The program diagram in the case of equipping the speed light	M 6
14.	The control for film advance / wind-up	M 7
①	The control to stop a film	M 7
②	The reference position	M 8
③	The position to stop	M 8
④	Loading a film, film loading operation	M 8
⑤	The figure of sequence/Parallel drive	M 9
	The figure of sequence/Serial drive	M 10
15.	Sequence error	M 11
16.	The operational differences for aperture mode on between F5 and F100	M 12

Specifications

1. Photometry

The pattern on photo detector




Photo detector : 10-division multiple segment SPD

Photometry performance : Multiple pattern photometry : EV 0 to 21

Center-weighted metering : EV 0 to 21

Spot metering : EV 3 to 21

In use of 50/1.4 lens in accordance with ISO100

2. TTL auto-flash control

Photo detector : 5-segment TTL multi sensor

Film speed : ISO 25 to 1000 guaranteed

3. A F

TTL phase difference detection method using the AP-4 module

Metering performance

Limit of measured luminance	Limit of open aperture value F
EV -1 to +19 under room temp., in accordance with ISO 100	F 1.2 to 5.6

4. Finder

Finder screen	B-type clear mat screen III
Superimpose screen	With photometry and metering functions
Possibility of finder replacement	Impossible
Possibility of screen replacement	Possible for B-type and E-type alone : No compatibility with F90X's
Finder field frame ratio	Approximately 96 % in both length (50mm Lens, ∞)
Diopter	-3 ~ +1 Dpt
Eyepoint	21.1 mm in response to -1 Dpt

5 .In-finder LCD back light

Using the yellow-green LED, back light shall apply.

Its luminance varies according to any photometry value(s).

6 .Superimpose display

LED light shall apply to the five micro prism in response to the AF area on the dedicated screen.

Its luminance varies according to any photometry value(s).

7 .The switches for mechanism

Name of switch	Arranged position
Rear cover switch	On the rear cover open/close key
Sync. switch	In the shutter unit
Sequence switch	In the sequence unit
Film detection switch	In the F detection unit
Rear curtain switch	In the shutter unit
Battery identification switch	On the grip of rear body
Battery release switch	On the grip of rear body
Power pack release switch a	On the bottom of rear body
Power pack release switch b	On the bottom of rear body
Mirror latch switch	On the I base plate
Lens release switch	On the front body

8 .Preview function

By forcibly pressing the preview button, the preview function starts to work.


Then, the aperture mode shall be controlled by any controlled aperture value(s) without mirror-up mode.

During the preview function, any aperture value displayed just before the commencement of preview mode shall be maintained.

Then, any others such as shutter speed lock and exposure indicator shall not be displayed.

Besides, even if the exposure mode changes during the preview, the displayed aperture value shall be maintained and then the displayed aperture value changes after canceling the preview function.

The figure of preview sequence



- ① According to the ON signal from the preview switch, conduction shall be started to the mirror latch magnet and to the front and rear shutters¹ magnets.
- ② As soon as the mirror latch switch detecting the latch mode of mirror is turned on, the conduction shall be stopped.
- ③ As soon as the mirror latch switch is turned on, the aperture control starts after 10 ± 1 m sec.
- ④ The conduction to the shutter magnet shall be maintained until the solenoid is turned off for the second time.
- ⑤ While pressing the preview button, the preview mode is maintained.

Then, select more delayed timing from either ¹timing to output the off-signal from the preview switch¹ or ¹timing to output the Tpd1¹, and turn on the solenoid.

Then, the preview mode goes to the sequence cancellation mode.


$$Tpd1 = 30 \pm 1 \text{ (0 to 100) mse}$$

- ⑥ The sequence motor shall be operated to drive after 12 m sec from the sequence switch¹s OFF signal.

- ⑦ After Tpd 2 from the sequence switch¹s ON signal, the conduction starts to the solenoid.

$$Tpd 2 = 30 \pm 1 \text{ (0 to 100) mse}$$


9 .The contacts for power pack



The figure for the bottom of camera

No.	Function of each contact
①	For command dial b on vertical position
②	For command dial a on vertical position
③	For AF operation
④	For shutter release from vertical position
⑤	For battery identification 0
⑥	For pre-release from vertical position
⑦	For battery release
⑧	For power pack change-over switch

1 0 .The contacts on the rear cover for connection with the camera




No.	Function of each contact
①	G ND
②	AF area mode
③	Focus area selector for left position
④	Focus area selector for upper position
⑤	Focus area selector for right position
⑥	Focus area selector for lower position

1 1 .Shutter

- (1) Copal Company Ltd.-made CHS-EM III Unit shutter
 (2) Max. speed 1/8000 sec. Sync. 1/250 sec.

1 2 .Program diagram




The pulse shows the line which goes 1-step further to the lower shutter speed in the program shift.

Program shift coverage

Program shift

- ① For the program shift, while constantly maintaining the EV value, the aperture value and the shutter speed shall be varied in order to change the diagram.
- ② The program shift shall be made by shifting the program diagram in the shutter speed direction.
In this accord, it shall be regarded impossible to make such a shift going beyond each control limit in the open aperture mode and the minimum aperture mode.
- ③ The shift shall be made for the program diagram even at the control limit.
- ④ In the program shift, ± 5 [EV] shall be specified the limit for both of the aperture value and the shutter speed.

1 3 .The program diagram in the case of equipping the speed light



The program shift in the case of equipping the speed light


- ① For the program shift, while constantly maintaining the EV value, the aperture value and the shutter speed shall be varied in order to change the diagram.
- ② The program shift shall be made by shifting the program diagram in the shutter speed direction.
In this accord, it shall be regarded impossible to make such a shift going beyond each control limit in the open aperture mode and the minimum aperture mode.
- ③ The shift shall be made for the program diagram even at the control limit.
- ④ In the program shift, ± 5 [EV] shall be specified the limit for both of the aperture value and the shutter speed.
- ⑤ As an example, in case of conducting the program shift in the conditions of "EV=20" and "- 2 [EV] as the shutter speed" , the pulse shall be controlled as shown in the diagram above.

1 4 .The control for film advance / wind-up


By driving the film advance motor in the right and normal operation direction, the spool drives in the regular advancing direction in order to wind up the film.

The quantity of film advance shall be controlled by monitoring the output from the film advance PI interlocking the move of sprocket.

*In response to 1-frame advance from a film, the 28-edge light shield and the 72-edge signal generate from the film advance PI.



The control to stop a film



A : Speed monitoring realm A

B : Speed monitoring realm B

C : Tolerance for stop position error : The first 8-edge from the beginning of a loaded film is automatically wended.

D : The designated / duty drive finishes from the reference position to the 42nd edge position as shown in the figure above.

The reference position

The position just after completion of detecting the 28-edge light shield area shall be specified as the reference position.

The position to stop

The 44th edge position from the reference position including the over-run shall be specified as the stop position.

Tolerance : 44 ± 2 edges

Stop servo

In response to changeable film advance speed caused by the power supply voltage, in order to constantly maintain the speed to stop, the film advance speed shall be monitored.


Then, the speed at the brake point shall be almost equally made by the operation control table in compliance with the monitored speed.

Besides, in order to respond to the dispersion in final speed, the operation time spent for reverse current brake shall be controlled in compliance with the stop servo speed.


Loading a film, film loading operation

The film loading operation takes approximately 2.5 to 3.5 frames.


The camera automatically starts to count from the 3rd frame stop position as the 1st ex.



The figure of sequence



Serial drive



1 5 .Sequence error

Sequence error	Condition(s) to cause the error
Mirror-up time-out	Even after 110 (± 10) m sec. from driving of the sequence motor, the sequence switch can not be turned on.
Mirror-down time-out	Even after 400 (± 20) m sec. from turning on the sequence motor after the shutter curtain operation, the sequence switch can not be turned on.
Front curtain release time-out	After canceling the close mode of shutter front curtain magnets, it takes more than 8 m sec. to turn on the contact X.
Troubled switch for shutter rear curtain switch	Before driving the sequence motor in the mirror-up mode, the shutter rear curtain switch is turned on.
Malfunction on sequence switch	In the condition that the solenoid is turned on once or twice, the sequence switch can not be switched from ON-mode to OFF-mode.
Troubled sequence switch	Before driving the sequence motor, the sequence switch is turned on.
Troubled sync. switch	Before the mirror-up operation, the sync. switch is turned on.
Preview time-out	Even after 500 m sec. from turning on the mirror latch solenoid, the mirror latch switch can not be turned on in the preview operation mode.
Sequence error during preview	Any sequence error(s) other than on the mirror latch switch happens in the preview operation mode.
Malfunction on shutter rear curtain switch	After canceling the close mode of shutter rear curtain magnets, it takes more than 12 m sec. to turn on the shutter rearcurtain switch.
Aperture control err	In case of more than 13-pulse difference(s) between the aperture control target pulse and the generation pulse. In this case, there is no recovery mode although "Err" is displayed.

1 5 . The operational differences for aperture mode on between F5 and F100

For regular set-up			
condition/mode		F5	F100
Built-in CPU lens	Sub command dial/set-up	The aperture ring shall be set to minimum.	The aperture ring shall be set to minimum.
	display	1/3 Step	1/3 Step
	Aperture ring / set-up	Possible	Impossible ; Locked shutter release mode
n o n - C P U lens	display	F-- Possible to check the aperture value through the direct-vision window	FEE No presence of direct-vision window
	Command dial / set-up	Impossible	Impossible
	Aperture ring / set-up	Possible	Possible
	display	F-- Possible to check the aperture value through the direct-vision window	F-- No presence of direct-vision window

For set-up in the unavailable command dial under the custom-setting mode			
condition/mode		F5	F100
Built-in CPU lens	Aperture ring / set-up	Possible	Possible
	display	F-- Possible to check the aperture value through the direct-vision window	1 Step
n o n - C P U lens	Aperture ring / set-up	Possible	Possible
	display	F-- Possible to check the aperture value through the direct-vision window	F-- No presence of direct-vision window

Disassembly

1.	Exterior	D 1
	Grip rubber, rubber on the rewind side, cover base plate	D 1
	Bottom cover	D 2
	Top cover	D 2
2.	Separation of the front body from the rear body	D 3
	Connector / solder bridge	D 3
	Separation of the front body from the rear body	D 4
3.	Rear body	D 4
	Rear C/D unit	D 4
	Remote terminal	D 5
	DC/DC circuit board	D 5
	Sequence unit, spool	D 6 ~ D 8
	Shutter unit	D 8
	Bottom base plate	D 9
	Film advance unit	D 9
	Film advance detection unit, sprocket	D 1 0
	Rear cover open/close key	D 1 0
	DX/DB F P C	D 1 1
	Rewind unit	D 1 2
	Power FPC	D 1 2
	Grip	D 1 3
	Film detection switch unit	D 1 4
	Other parts	D 1 4
4.	Front body	D 1 5
	Diopter adjuster unit	D 1 5
	Main printed circuit board	D 1 5
	Light baffle plate	D 1 6
	Prism box	D 1 7
	Horizontal AF lever, AF unit	D 1 8
	Bayonet mount, apron	D 1 8
	Attachable lens switch unit, AF/M switch circuit board	D 1 9
	Lens release button unit, lens release base plate	D 1 9
	AF driving unit	D 2 0
	Preview unit	D 2 0 ~ D 2 1
	Mirror box	D 2 2

Others	D 2 2
I base plate, L base plate	D 2 3
5. Top cover	D 2 3
Front C/D unit	D 2 3
Release switch unit	D 2 4
Front C/DFPC unit	D 2 4
Top cover FPC / film advance mode dial / triple operation buttons	D 2 5
Others	D 2 6
6. Rear cover	D 2 6


Disassembly • Assembly • Adjustment

- Note :**
- ① Be sure to remove battery before assembling.
 - ② When disassembling, pay attention to the wire arrangement and mounting positions and types of screw to be removed.
 - ③ Be sure you are grounded when holding electric parts because static electricity exerts serious adverse effects on IC's.


Disassembly

1. Exterior


Grip rubber, rubber on the rewind side, cover base plate



Bottom cover









Top cover




2. Separation of the front body from the rear body

Connector / solder bridge




Separation of the front body from the rear body**3. Rear body****Rear C/D unit**


Remote terminal




DC/DC circuit board






Sequence unit, spool





- Remove the screw #800.
- Slightly pull the power FPC #B11009 in the arrow direction and then remove four solder bridges.




- Raise up the power FPC #B11009 in the arrow direction.
- Remove the two solder .




**Shutter unit**



Bottom base plate




Film advance unit






Film advance detection unit, sprocket




Rear cover open/close key




DX/DB FPC




Rewind unit




Power FPC




Raise up the power FPC







Grip



Film detection switch unit




Other parts




4. Front body

Diopter adjuster unit




Main printed circuit board


- Remove the two connectors.




- Remove the four soldered areas.




- Remove the three connectors.




Light baffle plate





Prism box




Remove the superimpose holder.




Remove the in-finder display FPC/AE SPD.




Horizontal AF lever, AF unit




Bayonet mount, apron




Attachable lens switch unit, AF/M switch circuit board




Lens release button unit, lens release base plate



AF driving unit




Preview unit




● Remove the two soldered areas.



Gray : preview solenoid

Yellow : preview solenoid




- Slide the aperture reset link lever #378 in the arrow direction and then remove it.



Mirror box**Others**


I base plate, L base plate






Caution : Avoid to directly touch the black-painted area on the main mirror holder.
This is for the sake of protection against discolouration.


5. Top cover

Front C/D unit





Release switch unit**Remove the three soldered areas****Front C/DFPC unit****A double-sided adhesive tape****Remove the connector.**


#530

A double-sided adhesive tape


Top cover FPC / film advance mode dial / triple operation buttons



Others



6. Rear cover




Assembly and adjustment

1.	Rear cover	A 1
2.	Top cover	A 1
	Any other small part(s)	A 1
	Top cover FPC / film advance mode dial / triple operation buttons	A 2
	Front C/DFPC unit	A 3
	Release switch unit	A 3
	Front C/D unit	A 4
3.	Front body	A 4
	Any other small part(s)	A 4
	I base plate, L base plate	A 5
	How to adhere the main mirror	A 6
	Mirror box	A 6
	Preview unit	A 7
	AF driving unit	A 8
	Lens release button unit, lens release base plate	A 9
	Lens release switch unit, AF/M switch circuit board	A 9
	Bayonet mount, apron	A 10
	Horizontal AF lever, AF unit	A 10
	Height adjustment for the AF coupling	A 11
	Height adjustment for the aperture lever	A 11
	Prism box	A 12
	Angle adjustment of main mirror and sub mirror to 45°	A 13 ~ A 14
	Adjustment for the infinity alignment	A 15
	AE SPD position adjustment	A 15
	Light baffle plate	A 15
	Main printed circuit board	A 16
	Diopter adjuster unit	A 17
4.	Rear body	A 18
	Any other part(s)	A 18
	F detection switch	A 18
	Grip	A 19
	Power FPC	A 19
	Rewind unit	A 20
	DX/DB F P C	A 21
	Rear cover open / close key	A 22

Film advance detection unit, sprocket	A 2 2
Film advance unit	A 2 3
Bottom base plate	A 2 4
Shutter unit	A 2 4
Sequence unit, spool	A 2 5 ~ A 2 7
DC / DC circuit board	A 2 7
Remote terminal	A 2 8
Rear C/D unit	A 2 8
5 . Mounting and fixing the front body on to the rear body	A 2 9
Fixing the front body to the rear body	A 2 9
Where to connect the connectors / where to solder the solder bridge	A 2 9
Adjustment for the bodyback	A 3 0
6 . Exterior	A 3 0
Top cover	A 3 0
Adjustment through PC	A 3 1
AF adjustment	A 3 2
Bottom cover	A 3 3
Grip rubber, rewind-sided rubber, cover	A 3 3
Adjustment through PC operation required at replacement of part(s)	A 3 4

Assembly and adjustment



1. On the rear cover




2. On the top cover

Any other small part(s)


Position to attach the eyepiece frame



Top cover FPC / film advance mode dial / triple operation buttons




- Pass the triple operation buttons' FPC through the hole on top cover FPC.




- Fit the photometry mode dial's projection into the notch on photometry mode change plate #585 and fix them together.


Front C/DFPC unit



Release switch unit




Front C/D unit




3. Front body


Any other small part(s)




- Apply the oil barrier to the diagonal-lined area and the arrow areas.




I base plate, L base plate



Caution : Avoid to directly touch the black-painted area on the main mirror holder.
This is for the sake of protection against discolouration.





- Drive the ratchet gear #B336 one unclockwise and then fix it on the I base plate.



The position to hook the spring




How to adhere the main mirror




A direction to put aside

Note : In case of replacement of the main mirror, be sure to perform the 45-degree of angle adjustment between the main mirror and the sub mirror.
For more details, refer to the pages A 13 to 14.

Mirror box





Preview unit



- Lower the preview slide lever #369 to the position described in the figure above.
- Fit the tip of mirror-up latch driving lever #356 into the \square -shaped area on the preview slide lever #369.

Then, assemble the preview unit.






Place any extra lead wire(s) to beneath the solenoid.

● Solder two points.

Gray : Preview solenoid


Yellow : Preview solenoid

AF driving unit




721×2

Lens release button unit, lens release base plate




Lens release switch unit, AF/M switch circuit board






Where the black lead wire should go


Bayonet mount, apron



Horizontal AF lever, AF unit




The position to hook the spring

Height adjustment for the AF coupling

- ① Set the AF switch lever to [S].

Then, press the (attachable lens button) two or three times and measure the height of AF coupling axis #931.

- ② Adjust the height of AF coupling axis #931 using the screw #948.
 ③ Be sure that when adjusting the height of (attachable lens pin) to 0.4 mm, the AF coupling axis should not be higher than the bayonet surface.
 ④ After adjustment, fix the screw #491 by the Screw Lock.

Height adjustment for the aperture lever




- Using the tool J18004, measure the height of aperture lever.

In the case of out-of-standard found from the measured result(s), adjust the height by rotating the eccentric pin. After adjustment, shift the mirror-up vertical lever two or three times and check the height of aperture lever.


Standard : 3.4 ± 0.1 mm

- In the situation that the solenoid adsorption is taken off from the aperture control unit, adjust the aperture reset lever eccentric pin to make a gap between #378 and #383 in the size of 0.2 to 0.29 mm.
- Shift the reset lever to the bayonet side and then reset the aperture control solenoid.
- Apply the grease to beneath #378.


Prism box




Mount and fix the in-finder display FPC / AE SPD.



Mount and fix the super impose holder.



Angle adjustment of main mirror and sub mirror to 45°



[Tools in use]

1. For adjustment of the main mirror

① Collimator (J19002)

② Reflection mirror (J18197)

③ Optical parallel (J18037)

④ Hex. key in the size of 2 mm

2. For adjustment of the sub mirror

① Collimator (J19002)

② Sub mirror angle adjustment tool

(J18268-1)

③ Hex. key in the size of 2 mm


● Angle adjustment to settle 45-degree from the main mirror

Note :Adjust the accuracy of main mirror by lifting up and down the mirror two or three times before and after adjustment.


Avoid to directly touch the black colour-painted area by hand(s).

(1) Check the horizontal gap.

In case the horizontal gap size is out of standard, loosen the three screws #376 and a screw #717, and then shift the upper area of mirror box in back and forth in order for adjustment.



An eccentric pin on the I base plate
An eccentric pin on the L base plate



● Angle adjustment to settle 45-degree from the sub mirror

Note : Adjust the accuracy of main mirror by lifting up and down the mirror two or three times before and after adjustment.

(1) Check the vertical gap.

In the out-of-standard case, adjust the gap by driving the eccentric screw for sub mirror adjustment.

Standard

	Main mirror	Sb mirror
Horizontal gap	within $0 \pm 20'$	
Vertical gap	within $0 \pm 5'$	within $0 + 5'$
Distortion	within $\pm 8'$	

(2) Check the vertical gap.

Note : The eccentric pins for adjusting the main mirror are arranged on both the I and L base plates. In this accord, just in case the vertical gap is out of standard, these eccentric pins shall be used for adjustment.

① Drive the eccentric pin on the L base plate.

Then, settle the mirror not to touch the eccentric pin.

② Drive the eccentric pin on the I base plate in order to adjust the vertical gap to come within the standard.

③ After the adjustment, drive the I base plate's eccentric pin in order to settle it in negative 10' position from where is settled in the above adjustment column ②.

④ Drive the eccentric pin on the L base plate in order to adjust the vertical gap to come within the standard.

⑤ Comparing to the eccentric pin on the I base plate, the eccentric pin on the L base plate is placed on 10' in negative side and it causes to create a gap against a mirror.

The gap functions to absorb a bounce from the mirror.

Adjustment for the infinity alignment


- Using the standard lens J18010, adjust the infinity mark to align within ± 0.03 mm.

How to adjust

Adjust the washer #843 for prism box.

For more details, refer to the figure in the page A13.

AE SPD position adjustment



① Apply a high luminance light to AE SPD in order to reflect the AE SPD pattern on the main mirror.

② As shown in the left figure, fit the AE SPD on the focus frame.

Then, the AE SPD should be parallel to the main mirror.



③ After adjustment, fix the AE SPD unit by two screws #734.

For more details, refer to the figure in the page A 12.


④ Solder #436 on the in-finder display FPC.

For more details, refer to the figure in the page A 13.

Light baffle plate




L base plate





I base plate

Main printed circuit board





- Place #282 between TTL FPC and the L base plate mold.

How to crease on the main PCB




- Connect three connectors.



- Solder the solder bridge.
- Connect two connectors.


Diopter adjuster unit



- Fit the #B421 axis into the guide groove on the diopter adjuster unit #B658.


4. Rear body

Any other part(s)




F detection switch


Pass two lead wires for the F detection switch through this hole.




Grip




Power FPC








Rewind unit




- Maintain to set the clutch lever free in the arrow direction, and simultaneously mount and fix the clutch gear.

DX/DB F P C




Rear cover open / close key





Film advance detection unit, sprocket

Apply the grease G7100 on to each gear's cog





Appropriate gearing






- Along with the driving of sprocket #56 after fixing it, the gear on the film advance detection unit should drive simultaneously.




- Set the film holder roller inside the spool chamber and simultaneously mount and fix the clutch gear.

Bottom base plate





Apply the gear G7100 on to each gear axis, each gear's cog and both ends of #166

Shutter unit





Sequence unit, spool


The start position on the upper SQ unit




- Mount and fix the upper SQ unit on the lower SQ unit.




Where the lead wires for film advance motor should go



Pass two lead wires for the film advance motor through beneath the sequence FPC and bring the wires to the front side of sequence unit.




- Lift up the power FPC #B11009 in the arrow direction.
- Solder two lead wires.
- Return the power FPC #B11009 to the original position.




- Slightly pull the power FPC #B11009 in the arrow direction "A" and then solder four lead wires.
- Drive and fix the screw #800.
- Place any extra lead wire(s) to beneath the solenoid.


 DC / DC circuit board



Remote terminal




Rear C/D unit





5. Mounting and fixing the front body on to the rear body

Fixing the front body to the rear body




Where to connect the connectors / where to solder the solder bridge





Adjustment for the bodyback



- Measure from the bayonet surface to the external rail.

The X - marked positions are where to be measured.


Standard : 46.67 ± 0.02 mm / Tolerance for flatness :

within 0.02 mm

- In any out-of-standard case(s), place the washer between the rear body and the front body and then adjust it.


6. On the exterior

Top cover



Adjustment through PC

How to connect with each other



Conduct each adjustment in accordance with the adjustment software instructions on PC screen.

1. Adjustment for temperature detection voltage
2. AE adjustment
3. Inspection for aperture mode
4. M1 / 8000 adjustment
5. TTL adjustment

Note : Be sure to utilize either "F90" or "N90" oriented camera's shutter curtain.

6. Battery check adjustment

Confirmation of the battery check display mode

After adjusting the battery check, input below-mentioned each voltage data to the camera and then check the external LCD mode.

Note : Conduct the inspection by switching each voltage in order of No. 1 to 5.

External LCD mode	Set up voltage from the stabilized power supply	
	① 4.7V	⑤ 5.1V
	② 4.5V	④ 4.7V
	③ 4.3V	

AF adjustment

(Inspection and adjustment items)

- ① Inspection and adjustment for the AF accuracy : whole item shall be adjusted.
- ② YAW, PITCH
- ③ Lark adjustment
- ④ CCD output

(Tools in use)

1. For adjustment of whole item :

The tool(s) used for the AE-oriented adjustment shall be utilized.

2. For check of the AF accuracy

- ① Z adjustment lens J18266 for F5
- ② AF adjustment stand J15259
- ③ Z lens holder J15280, or position conversion adapter J15271 for tripod socket
- ④ AF chart J18237 for F5
- ⑤ Lighting box J15264 for high frequency

3. For adjustment of yaw and pitch

- ① The whole tool used for the check of AF accuracy just as mentioned above
- ② Adjustment tool for yaw and pitch J18230


4. For adjustment of lark

The whole tool used for the check of AF accuracy just as mentioned above


5. For adjustment of CCD output

AF 50/1.4S lens

Bottom cover



Grip rubber, rewind-sided rubber, cover




Adjustment through PC operation required at
replacement of part(s)


Parts replaced	Items of adjustment	Start from the adjustment for temp. detection voltage	AE accuracy	Aperature accuracy	M 1/8000	TTL accuracy	BC voltage	AF accuracy
Shutter unit					○			
Main PCB unit	○	○	○	○	○	○	○	○
AF base plate unit								○
TTL SPD unit	○					○		○
DC/DC circuit board							○	


Electric circuit

WIRING FIGURE	E 1
CIRCUIT DIAGRAM	E 2
MAIN P. C. B.	E 3 ~ E 6
TOP COVER FPC	E 7 ~ E 9
TTL FPC	E 10 ~ E 12
SEQUENCE FPC	E 13 ~ E 14
POWER FPC	E 15 ~ E 17
APERTURE FPC	E 18 ~ E 21
SHUTTER FPC	E 22
DX/DB FPC	E 23 ~ E 25
FILM ADVANCE PI FPC	E 26 ~ E 27
LENS CONTACT FPC	E 28
A F-P I FPC	E 29
TRIPLE OPERATIONS FPC.....	E 30
10 PIN TERMINAL FPC	E 31 ~ E 33
S · I FPC	E 34
REAR COVER FPC	E 35
REAR COMMAND DIAL FPC	E 36
FRONT COMMAND DIAL FPC	E 37
METERING/IN LCD FPC.....	E 38 ~ E 39


実体配線図 WIRING FIGUR









表面部品実装図
Surface parts mount figure



裏面部品実装図
Reverse parts mount figure




表面パターン図
Surface pattern figure





裏面パターン図
Reverse pattern figure

上カバーFPC
TOP COVER FPC




表面部品実装図
Surface parts mount figure






TTL FPC




表面部品実装図 Surface parts mount figure


表面パターン図
Surface pattern figure




裏面パターン図
Reverse pattern figure




シーケンス FPC
SEQUENCE FPC




表面パターン図
Surface pattern figure



表面部品実装図
Surface parts mount figure





表面パターン図
Surface pattern figure




裏面パターン図
Reverse pattern figure


絞り FPC
APERTURE FPC








表面パターン図
Surface pattern figure




シャッターFPC
SHUTTER FPC




表面パターン図
Surface pattern figure


DX・DB FPC




表面部品実装図
Surface parts mount figure




表面パターン図
Surface pattern figure




裏面パターン図
Reverse pattern figure



給送-P I F P C
FILM ADVANCE PI FPC




表面部品実装図
Surface parts mount figure




表面パターン図
Surface pattern figure

レンズ接点FPC
LENS CONTACT FPC




F - P I F P C




表面パターン図
Surface pattern figure

三つ葉FPC
Triple operations FPC




表面パターン図
Surface pattern figure


10ビンターミナルFPC
10 PIN TERMINAL FPC



表面部品実装図
Surface parts mount figure


裏面部品実装図
Reverse parts mount figure






表面パターン図
Surface pattern figure

S · I F P C




表面パターン図
Surface pattern figure




表面パターン図
Surface pattern figure

後コマンドダイヤルFPC
REAR COMMAND DIAL FPC




表面パターン図
Surface pattern figure

前コマンドダイヤルFPC
FRONT COMMAND DIAL FPC




表面パターン図
Surface pattern figure


測光／内LCD FPC
Metering/In LCD FPC



表面部品実装図
Surface parts mount figure



表面パターン図
Surface pattern figure



裏面パターン図
Reverse pattern figure

JUL. 8, 1999

F100 EEPROM MAP

ADDRESS	CONTENTS	VER.4.XX		REMARKS
32 (0020)	(TTL LEVEL)	0 (00)		UNUSED FOR ADJUSTMENT
33 (0021)	TTL FLASH GAMMA	135 (87)		
34 (0022)		110 (6E)		
38 (0026)		110 (6E)		
39 (0027)	TTL MONITOR PRE FLASH GAMMA	120 (78)		
40 (0028)		135 (87)		
44 (002C)	TTL MONITOR PRE FLASH LEVEL	135 (87)		
(002D)	CAMERA CONTROL DATA	72 (48)		
(002E)	〃	197 (C5)		
(002F)	〃	0 (00)		
(0030)	〃	39 (27)		
49 (0031)	BC ADJUSTMENT	122 (7A)		
50 (0032)	TEMPERATURE DETECTION ADJUSTMENT DATA	2 (02)		
51 (0033)	〃	250 (FA)		
52 (0034)	〃	1 (01)		
53 (0035)	〃	42 (2A)		
(0036)	BC ADJUSTMENT	102 (66)		UNUSED FOR ADJUSTMENT
(0037)	〃	92 (5C)		〃
(0038)	〃	96 (60)		〃
(0039)	〃	86 (56)		〃
(003A)	〃	0 (00)		〃
(003B)	〃	0 (00)		〃
(003C)	〃	106 (6A)		〃
(003D)	〃	89 (59)		〃
(003E)	〃	102 (66)		〃
(003F)	〃	84 (54)		〃
(0040)	〃	2 (02)		〃
(0041)	〃	209 (D1)		〃
(0042)	〃	147 (93)		〃
(0043)	〃	133 (85)		〃
(0044)	〃	143 (8F)		〃
(0045)	〃	122 (7A)		〃



ADDRESS	CONTENTS	VER.4.XX	REMARKS
(0046)	BC ADJUSTMENT	1 (01)	UNUSED FOR ADJUSTMENT
(0047)	"	44 (2C)	"
(0048)	"	155 (9B)	"
(0049)	"	129 (81)	"
(004A)	"	153 (99)	"
(004B)	"	113 (71)	"
(004C)	"	4 (04)	"
(004D)	"	179 (B3)	"
78 (004E)	M1/8000 ADJUSTMENT DATA	0 (00)	
79 (004F)	"	0 (00)	
(0050)	CAMERA CONTROL DATA	40 (28)	
(0051)	"	45 (2D)	
(0052)	"	5 (05)	
(0053)	"	12 (0C)	
(0054)	"	5 (05)	
(0055)	"	19 (13)	
(0056)	"	5 (05)	
(0057)	"	11 (0B)	
(0058)	"	11 (0B)	
(0059)	"	6 (06)	
(005A)	"	11 (0B)	
(005B)	"	11 (0B)	
(005C)	"	6 (06)	
(005D)	"	0 (00)	
(005E)	"	0 (00)	
(005F)	"	7 (07)	
(0060)	"	0 (00)	
(0061)	"	0 (00)	
(0062)	"	15 (0F)	
(0063)	"	1 (01)	
(0064)	"	50 (32)	
(0065)	"	30 (1E)	
(0066)	"	60 (3C)	
(0067)	"	100 (64)	
(0068)	"	70 (46)	
(0069)	"	150 (96)	
(006A)	"	6 (06)	
(006B)	"	41 (29)	



ADDRESS	CONTENTS	VER.4.XX		REMARKS
(006C)	CAMERA CONTROL DATA	30 (1E)		
(006D)	"	30 (1E)		
(006E)	"	43 (2B)		
(006F)	"	145 (91)		
(0070)	"	166 (A6)		
(0071)	"	30 (1E)		
(0072)	"	6 (06)		
(0073)	"	0 (00)		
(0074)	"	25 (19)		
(0075)	"	5 (05)		
(0076)	"	11 (0B)		
(0077)	"	6 (06)		
(0078)	"	50 (32)		
(0079)	"	50 (32)		
(007A)	"	36 (24)		
(007B)	"	47 (2F)		
(007C)	"	26 (1A)		
(007D)	"	50 (32)		
(007E)	"	19 (13)		
(007F)	"	2 (02)		
(0080)	"	3 (03)		
129 (0081)	FILM TONGUE	63 (3F)		
130 (0082)	"	125 (7D)		
(0083)	CAMERA COMTROL DATA	5 (05)		
(0084)	"	10 (0A)		
133 (0085)	"	128 (80)		
(0086)	"	255 (FF)		
(0087)	"	0 (00)		
(0088)	"	1 (01)		
(0089)	"	104 (68)		
(008A)	"	255 (FF)		
(008B)	"	88 (58)		
(008C)	"	32 (20)		
(008D)	"	0 (00)		
142 (008E)	AE LEVEL	128 (80)		
151 (0097)		128 (80)		
152 (0098)	AE GAMMA	128 (80)		



ADDRESS	CONTENTS	VER.4.XX		REMARKS
153 (0099)	AE RANGE	128 (80)		
154 (009A)		0 (00)		
	AF ADJUSTMENT			
1605 (0645)		0 (00)		
1606 (0646)	〃	119 (77)		
1607 (0647)	〃	85 (55)		
1608 (0648)	〃	34 (22)		
1608 (0649)	〃	34 (22)		
1610 (064A)	〃	102 (66)		
1611 (064B)	〃	102 (66)		
1612 (064C)	〃	119 (77)		
1613 (064D)	〃	170 (AA)		
1614 (064E)	〃	102 (66)		
1615 (064F)	〃	68 (44)		
1616 (0650)	〃	119 (77)		
1617 (0651)	〃	170 (AA)		
1618 (0652)	〃	102 (66)		
1619 (0653)	〃	68 (44)		
1620 (0654)		0 (00)		
	〃			
1731 (06C3)		0 (00)		
1732 (06C4)	〃	0 (00)		
1733 (06C5)	〃	25 (19)		
1734 (06C6)		240 (F0)		
	〃			
1761 (06E1)		240 (F0)		
1762 (06E2)	CAMERA CONTROL DATA	64 (40)		
1763 (06E3)	〃	88 (58)		
1764 (06E4)	〃	47 (2F)		
1765 (06E5)	〃	64 (40)		
1766 (06E6)	〃	44 (2C)		
1767 (06E7)	〃	46 (2E)		
1768 (06E8)	〃	40 (28)		
1769 (06E9)	〃	58 (3A)		
1770 (06EA)	〃	28 (1C)		
1771 (06EB)	〃	40 (28)		
1772 (06EC)	〃	39 (27)		
1773 (06ED)	〃	54 (36)		



ADDRESS	CONTENTS	VER.4.XX		REMARKS
1774 (06EE)	CAMERA CONTROL DATA	28 (1C)		
1775 (06EF)	"	37 (25)		
1776 (06F0)	"	0 (00)		
1789 (06FD)	"	0 (00)		
1790 (06FE)	"	194 (C2)		
1791 (06FF)	"	7 (07)		
1792 (0700)	"	5 (05)		
1793 (0701)	"	245 (F5)		
1794 (0702)	"	248 (F8)		
1795 (0703)	"	0 (00)		
1796 (0704)	"	0 (00)		
1797 (0705)	"	0 (00)		
1798 (0706)	"	0 (00)		
1799 (0707)	"	51 (33)		
1800 (0708)	"	0 (00)		
1801 (0709)	"	0 (00)		
1802 (070A)	"	0 (00)		
1803 (070B)	"	170 (AA)		
1804 (070C)	"	5 (05)		
1805 (070D)	"	20 (14)		
1806 (070E)	"	4 (04)		
1807 (070F)	"	179 (B3)		
1808 (0710)	"	51 (33)		
1809 (0711)	"	58 (3A)		
1810 (0712)	"	0 (00)		
1811 (0713)	"	40 (28)		
1812 (0714)	"	16 (10)		
1813 (0715)	"	0 (00)		
1814 (0716)	"	0 (00)		
1815 (0717)	"	122 (7A)		
1816 (0718)	"	10 (0A)		
1817 (0719)	"	2 (02)		
1818 (071A)	"	4 (04)		
1819 (071B)	"	3 (03)		
1820 (071C)	"	240 (F0)		
1821 (071D)	"	246 (F6)		
1822 (071E)	"	2 (02)		



ADDRESS	CONTENTS	VER.4.XX		REMARKS
1823 (071F)	CAMERA CONTROL DATA	14 (0E)		
1824 (0720)	"	26 (1A)		
1825 (0721)	"	38 (26)		
1826 (0722)	"	50 (32)		
1827 (0723)	"	62 (3E)		
1828 (0724)	"	74 (4A)		
1829 (0725)	"	246 (F6)		
1830 (0726)	"	2 (02)		
1831 (0727)	"	14 (0E)		
1832 (0728)	"	26 (1A)		
1833 (0729)	"	38 (26)		
1834 (072A)	"	50 (32)		
1835 (072B)	"	70 (46)		
1836 (072C)	"	74 (4A)		
1837 (072D)	"	254 (FE)		
1838 (072E)	"	9 (09)		
1839 (072F)	"	26 (1A)		
1840 (0730)	"	38 (26)		
1841 (0731)	"	50 (32)		
1842 (0732)	"	62 (3E)		
1843 (0733)	"	74 (4A)		
1844 (0734)	"	58 (3A)		
1845 (0735)	"	5 (05)		
1846 (0736)	"	80 (50)		
1847 (0737)	"	32 (20)		
1848 (0738)	"	20 (14)		
1849 (0739)	"	23 (17)		
1850 (073A)	"	32 (20)		
1851 (073B)	"	51 (33)		
1852 (073C)	"	51 (33)		
1853 (073D)	"	104 (68)		
1854 (073E)	"	10 (0A)		
1855 (073F)	"	32 (20)		
1856 (0740)	"	64 (40)		
1857 (0741)	"	24 (18)		
1858 (0742)	"	36 (24)		
1859 (0743)	"	64 (40)		
1860 (0744)	"	32 (20)		



ADDRESS	CONTENTS	VER.4.XX		REMARKS
1861 (0745)	CAMERA CONTROL DATA	38 (26)		
1862 (0746)	"	64 (40)		
1863 (0747)	"	13 (0D)		
1864 (0748)	"	128 (80)		
1865 (0749)	"	25 (19)		
1866 (074A)	"	100 (64)		
1867 (074B)	"	205 (CD)		
1868 (074C)	"	26 (1A)		
1869 (074D)	"	1 (01)		
1870 (074E)	"	1 (01)		
1871 (074F)	"	0 (00)		
1872 (0750)	"	0 (00)		
1873 (0751)	"	0 (00)		
1874 (0752)	"	102 (66)		
1875 (0753)	"	63 (3F)		
1876 (0754)	"	102 (66)		
1877 (0755)	"	63 (3F)		
1878 (0756)	"	150 (96)		
1879 (0757)	"	20 (14)		
1880 (0758)	"	80 (50)		
1881 (0759)	"	200 (C8)		
1882 (075A)	"	0 (00)		
1883 (075B)	"	12 (0C)		
1884 (075C)	"	102 (66)		
1885 (075D)	"	63 (3F)		
1886 (075E)	"	6 (06)		
1887 (075F)	"	63 (37)		
1888 (0760)	"	6 (89)		
1889 (0761)	"	55 (35)		
1890 (0762)	"	137 (89)		
1891 (0763)	"	53 (35)		
1892 (0764)	"	6 (06)		
1893 (0765)	"	53 (35)		
1894 (0766)	"	137 (89)		
1895 (0767)	"	54 (36)		
1896 (0768)	"	3 (03)		
1897 (0769)	"	232 (E8)		
1898 (076A)	"	40 (28)		



ADDRESS	CONTENTS	VER.4.XX	REMARKS
1899 (076B)	CAMERA CONTROL DATA	40 (28)	
1900 (076C)	"	100 (64)	
1901 (076D)	"	0 (00)	
1902 (076E)	"	0 (00)	
1903 (076F)	"	0 (00)	
1904 (0770)	"	0 (00)	
1905 (0771)	"	0 (00)	
1906 (0772)	"	18 (12)	
1907 (0773)	"	132 (84)	
1908 (0774)	"	60 (3C)	
1909 (0775)	"	45 (2D)	
1910 (0776)	"	30 (1E)	
1911 (0777)	"	20 (14)	
1912 (0778)	"	0 (00)	
1913 (0779)	"	125 (7D)	
1914 (077A)	"	125 (7D)	
1915 (077B)	"	1 (01)	
1916 (077C)	"	0 (00)	
1917 (077D)	"	0 (00)	
1918 (077E)	"	48 (30)	
1919 (077F)	"	16 (10)	
1920 (0780)	"	58 (3A)	
1921 (0781)	"	0 (00)	
1922 (0782)	"	48 (30)	
1923 (0783)	"	16 (10)	
1924 (0784)	"	58 (3A)	
1925 (0785)	"	0 (00)	
1926 (0786)	"	48 (30)	
1927 (0787)	"	16 (10)	
1928 (0788)	"	58 (3A)	
1929 (0789)	"	0 (00)	
1930 (078A)	"	0 (00)	
1931 (078B)	"	200 (C8)	
1932 (078C)	"	7 (07)	
1933 (078D)	"	208 (D0)	
1934 (078E)	"	10 (0A)	
1935 (078F)	"	30 (1E)	
1936 (0790)	"	200 (C8)	





JUL. 8, 1999

F100 EEPROM MAP

ADDRESS	CONTENTS	VER.5.XX	REMARKS
32 (0020)	(TTL LEVEL)	0 (00)	UNUSED FOR ADJUSTMENT
33 (0021)	TTL FLASH GAMMA	135 (87)	
34 (0022)		110 (6E)	
	TTL FLASH LEVEL		
38 (0026)		110 (6E)	
39 (0027)		120 (78)	
40 (0028)	TTL MONITOR PRE FLASH LEVEL	135 (87)	
44 (002C)		135 (87)	
(002D)	CAMERA CONTROL DATA	197 (C5)	
(002E)	〃	39 (27)	
47 (002F)	BC ADJUSTMENT	122 (7A)	
48 (0030)	TEMPERATURE DETECTION ADJUSTMENT DATA	2 (02)	
49 (0031)	〃	250 (FA)	
50 (0032)	〃	1 (01)	
51 (0033)	〃	42 (2A)	
(0034)	BC ADJUSTMENT	102 (66)	UNUSED FOR ADJUSTMENT
(0035)	〃	92 (5C)	〃
(0036)	〃	96 (60)	〃
(0037)	〃	86 (56)	〃
(0038)	〃	0 (00)	〃
(0039)	〃	0 (00)	〃
(003A)	〃	106 (6A)	〃
(003B)	〃	89 (59)	〃
(003C)	〃	102 (66)	〃
(003D)	〃	84 (54)	〃
(003E)	〃	2 (02)	〃
(003F)	〃	209 (D1)	〃
(0040)	〃	147 (93)	〃
(0041)	〃	133 (85)	〃
(0042)	〃	143 (8F)	〃
(0043)	〃	122 (7A)	〃
(0044)	〃	1 (01)	〃
(0045)	〃	44 (2C)	〃



ADDRESS	CONTENTS	VER.5.XX	REMARKS
(0046)	BC ADJUSTMENT	155 (9B)	UNUSED FOR ADJUSTMENT
(0047)	"	129 (81)	"
(0048)	"	153 (99)	"
(0049)	"	113 (71)	"
(004A)	"	4 (04)	"
(004B)	"	179 (B3)	"
76 (004C)	M1/8000 ADJUSTMENT DATA	0 (00)	
77 (004D)	"	0 (00)	
(004E)	CAMERA CONTROL DATA	40 (28)	
(004F)	"	45 (2D)	
(0050)	"	5 (05)	
(0051)	"	19 (13)	
(0052)	"	11 (0B)	
(0053)	"	11 (0B)	
(0054)	"	6 (06)	
(0055)	"	11 (0B)	
(0056)	"	11 (0B)	
(0057)	"	6 (06)	
(0058)	"	7 (07)	
(0059)	"	15 (0F)	
(005A)	"	50 (32)	
(005B)	"	30 (1E)	
(005C)	"	60 (3C)	
(005D)	"	100 (64)	
(005E)	"	70 (46)	
(005F)	"	150 (96)	
(0060)	"	6 (06)	
(0061)	"	41 (29)	
(0062)	"	166 (A6)	
(0063)	"	30 (1E)	
(0064)	"	6 (06)	
(0065)	"	25 (19)	
(0066)	"	11 (0B)	
(0067)	"	6 (06)	
(0068)	"	50 (32)	
(0069)	"	36 (24)	
(006A)	"	47 (2F)	
(006B)	"	26 (1A)	



ADDRESS	CONTENTS	VER.5.XX	REMARKS
(006C)	CAMERA CONTROL DATA	19 (13)	
(006D)	"	3 (03)	
110 (006E)	FILM TONGUE	63 (3F)	
111 (006F)	"	125 (7D)	
(0070)	CAMERA CONTROL DATA	5 (05)	
(0071)	"	10 (0A)	
114 (0072)	"	128 (80)	
(0073)	"	255 (FF)	
(0074)	"	0 (00)	
117 (0075)		128 (80)	
	AE LEVEL		
126 (007E)		128 (80)	
127 (007F)	AE GUMMA	128 (80)	
128 (0080)	AE RANGE	128 (80)	
129 (0081)	AF ADJUSTMENT	0 (00)	
1580 (062C)		0 (00)	
1581 (062D)		119 (77)	
1582 (062E)	"	85 (55)	
1583 (062F)	"	34 (22)	
1584 (0630)	"	34 (22)	
1585 (0631)	"	102 (66)	
1586 (0632)	"	102 (66)	
1587 (0633)	"	119 (77)	
1588 (0634)	"	170 (AA)	
1589 (0635)	"	102 (66)	
1590 (0636)	"	68 (44)	
1591 (0637)	"	119 (77)	
1592 (0638)	"	170 (AA)	
1593 (0639)	"	102 (66)	
1594 (063A)	"	68 (44)	
1595 (063B)	"	0 (00)	
1596 (063C)		0 (00)	
1707 (06AB)		0 (00)	
1708 (06AC)		25 (19)	
1709 (06AD)		240 (F0)	



ADDRESS	CONTENTS	VER.5.XX	REMARKS
1736 (06C8)	AF ADJUSTMENT	240 (F0)	
1737 (06C9)		0 (00)	
	CAMERA CONTROL DATA		
1741 (06CD)		0 (00)	
1742 (06CE)	〃	58 (3A)	
1743 (06CF)	〃	20 (14)	
1744 (06D0)	〃	23 (17)	
1745 (06D1)	〃	32 (20)	
1746 (06D2)	〃	51 (33)	
1747 (06D3)	〃	10 (0A)	
1748 (06D4)	〃	32 (20)	
1749 (06D5)	〃	102 (66)	
1750 (06D6)	〃	36 (24)	
1751 (06D7)	〃	64 (40)	
1752 (06D8)	〃	38 (26)	
1753 (06D9)	〃	64 (40)	
1754 (06DA)	〃	13 (0D)	
1755 (06DB)	〃	128 (80)	
1756 (06DC)	〃	26 (1A)	
1757 (06DD)	〃	16 (10)	
1758 (06DE)	〃	102 (66)	
1759 (06DF)	〃	63 (3F)	
1760 (06E0)	〃	102 (66)	
1761 (06E1)	〃	63 (3F)	
1762 (06E2)	〃	128 (80)	
1763 (06E3)	〃	20 (14)	
1764 (06E4)	〃	80 (50)	
1765 (06E5)	〃	200 (C8)	
1766 (06E6)	〃	0 (00)	
1767 (06E7)	〃	12 (0C)	
1768 (06E8)	〃	102 (66)	
1769 (06E9)	〃	63 (3F)	
1770 (06EA)	〃	137 (89)	
1771 (06EB)	〃	53 (35)	
1772 (06EC)	〃	6 (06)	
1773 (06ED)	〃	53 (35)	
1774 (06EE)	〃	137 (89)	
1775 (06EF)	〃	54 (36)	





INSPECTION STANDARD AND TOOLS

- [1] Inspection standard R 1 ~ R 5
 - [2] Tools T 1
-
-

CONDITION FOR INSPECTION

Normal temperature : Temperature $20 \pm 5^\circ\text{C}$ Humidity $65 \pm 20\%$

Power source : 5.5 V 5 A or more at 0.4Ω load

Light source : 2,856 ° K

K coefficient : 1.16

1. INSPECTION STANDARD

1. The EV value in the description is the EV value of ISO100.
2. The symbol of EV conversion for errors is as follows. "+" is used for overexposure and "-" underexposure .
3. Cel 1 - cell 10 for metering are cells for 10-divided SPD as shown below.

On the finder.

Cell 1 : Center doughnut / Cell 2 : Left upper / Cell 3 : Right upper / Cell 4 : Left lower
 Cell 5 : Right lower / Cell 6 : Spot-center / Cell 7 : Spot-left / Cell 8 : Spot-right
 Cell 9 : Spot- upper / Cell 1 0 : Spot-lower

4. Cel 1 - cell 5 for metering are cells for 5-divided TTL SPD for TTL as shown below.

On the finder.

Cell 1 : Center / Cell 2 : Left upper / Cell 3 : Right upper / Cell 4 : Left lower
 Cell 5 : Right lower

Evaluation items	Standard	Remarks
Main mirror 4 5 ° position	Up and down Within 4 5 ' Left and right Within 2 5 ' Distortion Within 8 '	No gap when mirror-up J19002 · J18197 · J1803 Hexagonal key
Sub mirror 4 7.7 5 ° position	Up and down Within $-5 \frac{+10}{-25}$ ' Distortion Within 8 '	J19002 · J18268-1 Hexagonal key
Lens release pin	Protrusion height $1.4 \frac{+0.05}{-0.2}$ mm	
Lens contact	Contact width 1.5 ± 0.1 mm or more	
Aperture lever	Depth from bayonet surface 5.3mm~6.7mm 3.4 height (when using a tool)) 3.4 ± 0.1 mm Horizontal position $18.7 \frac{+0.35}{-0.30}$ mm	J18004
AF coupling MB F	Protrusion height 1.7 ± 0.2 mm Standard 46.67 ± 0.03 mm Parallel Within 0.03 mm Clearance between outside rail and inner rail 0.23 ± 0.02 mm Difference between inner rail and aperture surface 0.2 mm or more	J18001 Dial gauge
Film detection switch	Height from guide 2 ± 0.2 mm OFF position 0.3 mm or more Whole stroke should be lower than the sprocket surface.	
Infinity	$\pm 4.0''$ ($\pm 6.0 \mu\text{m}$)	J18010

Evaluation items	Standard			Remarks
Contacts of the rear cover	Hight Stroke			$2.5 \pm 0.15\text{mm}$ $1.35^{+0.3}_{-0.2}\text{mm}$
A F alignment	Y a w P i t c h			Center $0 \pm 4\text{ mrad}$ Side $0 \pm 10\text{ mrad}$ Center $0 \pm 5\text{ mrad}$ Side $0 \pm 10\text{ mrad}$
Focusing range	A F lighthing range Within $0 \pm 80 \sim 120\text{ }\mu\text{m}$			
AF assist lamp	Turn on the AF assist lamp under EV6			
Metering	AF50/1.4D	AMP	Error of recognition (EV0 ~ EV21) Within $\pm 0.5\text{ EV}$	
		CW	Error of recognition (EV0 ~ EV21) Within $\pm 0.5\text{ EV}$	
		S P O T	Error of recognition (EV3 ~ EV21)	
		5 area	Within $\pm 0.5\text{ EV}$	
Error of Metering mode	From CW AF50/1.4D AMP Within $\pm 1/3\text{ EV}$ (EV0 ~ EV10) S P O T Within $\pm 1/3\text{ EV}$ (EV3 ~ EV)			
Center weighted	$\Phi 1.2\text{ mm circle}$ AF50/1.4D 7.5 % or more			
Difference by focusing screen	Stnderd from B type focusing screen E type focusing screen Within $\pm 1/3\text{ EV}$			
Position of A E SPD	Stnderd from focusing screen Up and down and Left and right $0 \pm 0.5\text{ mm}$			
A E accuracy	Each A E mode and each Metering mode 1/8000 ~ 1/4000 Within $\pm 0.75\text{ EV}$ (Without AMP) (1/4000) ~ 1/2000 Within $\pm 0.5\text{ EV}$ (1/2000) ~ Within $\pm 0.4\text{ EV}$ Tolerance Within $\pm 0.3\text{ EV}$			
	Difference by A E mode Within $\pm 0.4\text{ EV}$			
	Difference by Metering mode Within $\pm 0.3\text{ EV}$			

Evaluation items	Standard	Remarks
A E - A accuracy (CW)	EV 1.5 F 8 (1/500)	Within ± 0.5 T v
	Tolerance	Within 0.3 T v
	EV 1.2 F 5.6 (1/125)	Within ± 0.5 T v
	Tolerance	Within 0.3 T v
	EV 6 F 2.8 (1/8)	Within ± 0.5 T v
	Tolerance	Within 0.3 T v
	EV 1.5 1/500 (F 8)	Within ± 0.5 A v
	Tolerance	Within 0.5 A v
A E - S accuracy (CW)	EV 1.2 1/125 (F 5.6)	Within ± 0.5 A v
	Tolerance	Within 0.5 A v
	EV 6 1/8 (F 2.8)	Within ± 0.5 A v
	Tolerance	Within 0.5 A v
	1/8000~1/4000	Within ± 0.6 5dT v
	(1/4000) ~1/2000	Within ± 0.3 5dT v
	(1/2000) ~ 3.0 秒	Within ± 0.2 dT v
	1/250	Within 4.14 ms $^{+0.2}_{-0.1}$ dT v
Shutter speed accuracy	Tolerance	
	1/8000~1/5000	Within 0.45 T v
	1/4000~1/2500	Within 0.3 T v
	1/2000~3.0 秒	Within 0.2 T v
	Front and rear curtain (21mm)	Within 2.58 ± 0.08 ms
	Time lag (21mm)	0.1 ~ 0.4 ms
	Allowance after turning ON (21mm)	1.1ms or more
Finder	Visual field rate	9.6 ± 2 %
	Prallax	Up and down and Left and right Within 0.5 mm
	Eye point	Distance to eyepiece lens 1.9 ± 2 mm
Consumption Standby current	Main switch OFF	6.0 μ A or less
	Do not push the off of operation button	1.00 μ A or less
	Main switch ON (Power OFF)	6.0 μ A or less
	Main switch ON (Power ON)	1.00 μ A or less
	Main switch ON (Illuminator ON)	3.30 mA or less
	Resistance of hotshoe and G ND	EV 1.2
		5.0 / 1.4
		EV 1.2
		5.0 / 1.4
		5.0 m Ω or less

Evaluation items	Standard	Remarks
B C level	Primary level Standard battery pack Alkaline battery × 4 MS - 1 3 For CR 1 2 3 MB - 1 5 Alkaline battery × 6 Ni-MN-15	Lower direction : 4.2 ± 0.2 V Restoring direction : 4.7 ± 0.2 V Lower direction : 4.5 ± 0.2 V Restoring direction : 5.0 ± 0.2 V Lower direction : 5.8 ± 0.2 V Restoring direction : 6.2 ± 0.2 V Lower direction : 6.5 ± 0.2 V Restoring direction : 7.2 ± 0.2 V
	Secondary level Standard battery pack Alkaline battery × 4 MS - 1 3 For CR 1 2 3 MB - 1 5 Alkaline battery × 6 MB - 1 5 Ni-MN-15	Lower direction : 4.1 ± 0.2 V Restoring direction : 4.5 ± 0.2 V Lower direction : 4.2 ± 0.2 V Restoring direction : 4.7 ± 0.2 V Lower direction : 5.5 ± 0.2 V Restoring direction : 6.1 ± 0.2 V Lower direction : 6.0 ± 0.2 V Restoring direction : 7.0 ± 0.2 V
Pre-release timer time	After pre-release switch OFF After release	6 ± 0.5 ms 1 ± 0.5 ms
Battery life on bulb mode	Alkaline battery × 4 LR 6 : 4 H or more Lithium × 4 FR 6 : 7 H or more Alkaline battery × 6 LR 6 : 8 H or more Lithium × 6 FR 6 : 10 H or more Ni-MN Pack : 4 H or more Lithium × 2 CR 1 2 3 : 3 H or more	
Image dimension 50 / 1.4 F5.6	Width $36^{+0.4}_{-0.6}$ mm Length $24^{+0.4}_{-0.6}$ mm R of corners R 0.4 mm or less	
Frame space	Winding S + C mode 2 ± 1.0 mm or less Winding CS mode 2 ± 1.0 mm or less	

2. Tools

1. Dedicated tools

There is provided only an adjustment software as a new tool for F 100.


In addition, the sub mirror angle adjustment tool J18268 for F 5 can be a commonly used tool for both of F100 and F5 by remodeling "J18268" to "J18268-1" by Service Planning Sec., Imaging Products Div.

Tool No.	Name of tool	Others
J18268-1	10-pin connector communication tool	For F5
J18266	Z adjustment lens	For F5
J18268-1	Sub mirror angle adjustment tool	For F5、F100
J18197	Reflection mirror	For F90
J18273	AF chart	For F5
J18296A	Inspection and adjustment software	For NEC 5.0 inch
J18296B	Inspection and adjustment software	For NEC 3.5 inch
J18296C	Inspection and adjustment software	For IBM 5.0 inch
J18296D	Inspection and adjustment software	For IBM 3.5 inch

2. Hand-made tool

Through remodeling the battery holder, it makes possible to mechanically change the battery identification switch mode and to supply the set voltage from the stabilized power source to the camera.

- ① Remove the three screws from the bottom of battery holder and then remove the two battery contacts.
- ② While removing the bottom of battery contacts, assemble the battery holder.
- ③ Make a hole on the bottom of battery holder.



- ④ As shown in the figure, remodel the battery contact in order to attach it on to the battery holder, and then fix it on the GND of battery holder by an adhesive.
- ⑤ Prepare two lead wires and connect them as shown in the figure.

